



**CLASSIC CLEAR UV  
PRODUCT CODE: 3-7122**

**PRODUCT DESCRIPTION**

3.5-mil high gloss flexible vinyl is an economical vinyl with solvent permanent solvent adhesive that is ideal for window graphics, point of purchase displays, decals, and other identification pieces. Solvent, eco-sol, latex and UV ink jet printable.

**APPLICATIONS**

- Point of purchase displays
- Window graphics

**FEATURES AND BENEFITS**

- Permanent solvent adhesive with ultraviolet light inhibitor
- Can be wet applied

**TECHNICAL DATA**

Face Material	3.5-mil flexible vinyl
Color and Finish	Gloss clear
Adhesive	07UV, permanent solvent
Liner	90# polycoated bleached kraft

**TYPICAL CHARACTERISTICS**

Target Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	70 oz.	90 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	1 year	
Outdoor Durability	3 years	

**CHEMICAL RESISTANCE**

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	N/A
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	Noticeable Lifting

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
May-14 Form 108-01 (1/99)