



CLASSIC MATTE LOW TACK BO PRODUCT CODE: 3-9109

PRODUCTION DESCRIPTION

Flexible vinyl that is printable with various digital equipment utilizing ink jet technology. Excellent for use in point-of-purchase, trade show displays, and window graphics.

APPLICATIONS

- Point of purchase
- Promotional displays
- Trade show displays
- Window graphics

FEATURES AND BENEFITS

- 3.4-mil white flexible vinyl, ultra low peel removable acrylic adhesive, 90# polycoated layflat liner.

TECHNICAL DATA

Face Material	3.4-mil flexible vinyl
Color and Finish	Matte white
Adhesive	Ultra low peel removable acrylic
Liner	90# polycoated bleached layflat

TYPICAL CHARACTERISTICS

Average Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> .2 lbs./inch	<u>24 hr.</u> .3 lbs./inch
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	3 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	Slight Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	NA
10% Ammonium Hydroxide (10 min)	Slight Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	Noticeable Lifting

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. Ritrama recommends 24 hours of outgasing time between printing and over laminating.
Dec-10 Form 108-01 (1/99)