



## CLASSIC WHITE MOUNT HIGH-TACK PRODUCT CODE: 4-0312

### PRODUCT DESCRIPTION

White mounting film designed for laminating permanently to the back of another printed substrate

### APPLICATIONS

- Adhering nameplates and backlit panels
- Point of purchase displays
- Promotional products

### FEATURES AND BENEFITS

- High-tack permanent adhesive on both sides

### TECHNICAL DATA

Face Material	2.3-mil polypropylene
Color and Finish	White
Adhesive	99, high-tack permanent acrylic on each side
Liner	60# differential

### TYPICAL CHARACTERISTICS

Adhesion Values - Ranges (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 32 – 48 oz.	<u>24 hr.</u> 40 – 55 oz.
Minimum Application Temperature Range	50°F to 120°F	
Service Temperature Range	-65°F to +225°F	
Shelf Life (@ 73°F, 50% RH)	1 year	
Outdoor Durability (ASTM G53)	6 months under limited light exposure	

### CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

May-14

Form 108-01 (1/99)