



CRYSTAL CLING 4 PRODUCT CODE: 4-0513

PRODUCT DESCRIPTION

This optically clear 4.0-mil polyester film is print treated for use with UV and conventional inks designed with a unique polymer technology that allows the film to cling to glass and other smooth substrates. The result is a very soft peel from glass that mimics static cling performance.

APPLICATIONS

- Window graphics
- Point of purchase display cases
- Protective film

FEATURES AND BENEFITS

- Mimics static cling without the environmental and processing concerns. This product meets the current standards of the Consumer Product Safety Improvement Act (CPSIA)
- UV ink jet compatible .
- Can be applied by the wet application method for improved aesthetics

TECHNICAL DATA

Face Material	4.0-mil polyester print treated
Color and Finish	Clear Gloss
Liner	3.0-mil polyester traction back

TYPICAL CHARACTERISTICS

Target Cling Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on glass)	<1 oz/in	<1 oz/in
Minimum Application Temperature	32°F	
Service Temperature Range	-40°F to +225°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability of film	2 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
Apr-13 Form 108-01 (1/99)