



## ECONOMY FLOOR TALKER PRODUCT CODE: 3-9829

### PRODUCTION DESCRIPTION

Ideal for temporary and short-term durability (6 months). This overlamine product is an excellent choice for economical floor graphics applications. This product is offered on a film liner for excellent wet out and is UL-410 classified for slip resistance

### APPLICATIONS

- Floor graphics
- Point of purchase displays
- Counter graphics

### FEATURES AND BENEFITS

- UL-410 classified for slip resistance
- Environmentally friendly
- Clear textured

### TECHNICAL DATA

Face Material	3.75-mil polyolefin
Color and Finish	Clear textured
Adhesive	FG, overlaminating permanent acrylic
Liner	1.2-mil clear film

### TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 65 oz.	<u>24 hr.</u> 75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	Indoor use only	

*\*Edge sealer can be applied to protect the edges of your graphics from potential lifting and curling that occurs from contamination or cleaning. The sealer should be tested to determine suitability with overlamine.*

### CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hr)	No Effect



The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
Dec-10