



ULTIMATE BRICK ACTION PRODUCT CODE: 4-0290

PRODUCT DESCRIPTION

Gloss white flexible vinyl with removable gray-pigmented adhesive with Licensed Air Flow Release Liner™ for easier, faster graphics installation on painted brick.

APPLICATIONS

- Painted brick
- Irregular wall surfaces

FEATURES AND BENEFITS

- Licensed Air Flow Release Liner™ for reduced wrinkling and air bubbles
- 7 year outdoor durable gloss white flexible vinyl
- Solvent gray removable adhesive

TECHNICAL DATA

Face Material	2.4-mil flexible vinyl
Color and Finish	White gloss
Adhesive	Gray pigmented removable acrylic
Liner	90# patterned Licensed Air Flow Release Liner™

TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 1.5 lbs.	<u>24 hr.</u> 2.5 lbs.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability (ASTM G53)	7 years	

Ritrama recommends the use of heat to help adhere film to recessed areas of the wall. Please test the anchorage of the paint before application.

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

Feb-11

Form 108-01 (1/99)