



ULTIMATE CLEAR MOUNT PRODUCT CODE: 3-9324

PRODUCT DESCRIPTION

Clear polyester with permanent solvent adhesive on each side combined with a 1.2-mil polyester liner on each side for excellent clarity. This clear mounting film is designed for laminating permanently to printed substrates.

APPLICATIONS

- Adhering nameplates and backlit panels
- Point of purchase displays
- Promotional products
- Window graphics

FEATURES AND BENEFITS

- Permanent solvent adhesive on both sides with high peel and good tack.

TECHNICAL DATA

Face Material	1.0-mil clear polyester
Color and Finish	Clear
Adhesive	22, permanent solvent on each side
Liner	1.2-mil polyester each side

TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 40 oz.	<u>24 hr.</u> 45 oz.
Static Shear (1/2-inch x 1/2-inch x 500 grams)	> 24 hours	
Minimum Application Temperature Range	50°F to 120°F	
Service Temperature Range	-65°F to +225°F	
Shelf Life (@ 73°F, 50% RH)	1 year	
Outdoor Durability	2 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

May-14

Form 108-01(1/99)