



ULTIMATE WINDOW MOUNT X
PRODUCT CODE: 4-0143

PRODUCT DESCRIPTION

Clear mounting film designed for laminating permanently to the front of a printed graphic substrate while utilizing a solvent removable adhesive with 90X Air Flow release liner for easy application on the other side of the clear film for temporary applications to windows.

APPLICATIONS

- Window graphics
- Point of purchase displays
- Promotional products
- Temporary graphics

FEATURES AND BENEFITS

- Solvent permanent on one side and solvent removable on the other side for temporary applications.

TECHNICAL DATA

Face Material	1.0-mil polyester
Color and Finish	Clear
Adhesives	ARS2, solvent removable medium tack
	13, permanent solvent one side
Liners	90X patterned Licensed Air Flow Release Liner™ on the removable side
	1.2-mil clear polyester on the permanent side

TYPICAL CHARACTERISTICS

Target Adhesion Values		<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	27	20 oz.	30 oz.
	13	40 oz.	50 oz.
Shear (1/2" x 1/2" x 500 gms.)		24 hrs.+	
Minimum Application Temperature		50°F	
Service Temperature Range		-65°F to +225°F	
Shelf Life (@ 73°F, 50% RH)		1 year	
<i>NOTE: Due to varying dimensional stability of paper this product is not recommended for use with paper stocks.</i>			
Outdoor Durability		2 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
Form 108-01(1/99)