



ULTRA GLOSS PRODUCT CODE: 4-0428

PRODUCT DESCRIPTION

High gloss clear flexible vinyl for long-term outdoor overlaminating applications such as vehicle wraps.

APPLICATIONS

- Vehicle wrap overlaminating
- General overlaminates
- Point of purchase displays

FEATURES AND BENEFITS

- 5 year outdoor durability
- 1-mil overlaminating adhesive with added ultraviolet light inhibitor

TECHNICAL DATA

Face Material	2.4-mil flexible vinyl
Color and Finish	Clear Gloss
Adhesive	07UV overlaminating permanent solvent
Liner	78# clay-coated smooth bleached kraft

TYPICAL CHARACTERISTICS

Average Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 50 oz.	<u>24 hr.</u> 75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor durability	5 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
Dec-11 Form 108-01 (1/99)